

INFUSION FLOW R91

LDPE/HDPE Infusion Flow Media

Features:

- Extruded Low/High Density Polyethylene (LDPE/HDPE) blend, 0.125 in (3.175mm) open diamond mesh capable of withstanding process temperatures of up to 250°F (121°C).
- Designed to assist resin flow to ensure complete substrate saturation during infusion or VARTM (Vacuum Assisted Resin Transfer Molding) process.
- Suitable use with polyester, vinyl-ester, and epoxy infusion resins.
- Will not fray or roll up at the ends when cut.

Properties:

Technical Data:	Typical Value:
Material Type	LDPE/HDPE blend
Max. use temperature	250°F (121°C)
Color	Red
Thickness	0.050 in (1.27mm)
Weight	4.14oz/yd ² (140.33g/m ²)

The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.

Availability:

- Standard roll size: 60" x 350'
- Non-standard widths and lengths are available upon request (minimum may apply).

Storage:

- Store in original packaging and protect from the environment.

Health & Safety:

- Handling of these products must conform to individual company guidelines and health and safety regulations.

Technology Marketing, Inc.

P: 801.265.0111 • F: 801.265.0184

6122 Stratler Street • Salt Lake City, UT 84107 USA • customerservice@tmi-slc.com • www.tmi-slc.com

ISO 9001:2015 & AS9120B Certified

Note: Data provided is for information only and does not constitute any warranty for the product as the conditions and varying methods of use are beyond our control. Technology Marketing Inc. shall not be liable for any special indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use or inability to use these materials. These materials are provided "as is" without warranty of any kind, either expressed or implied including, but not limited to the implied warranties of merchantability or fitness for a particular purpose