

# TMI-VV

## *Vacuum Valve, Small Footprint*

### Features:

- Blue anodized aluminum base plate to reduce or eliminate the disposal of during bag removal.
- Stainless steel knurled edge valve top threads easily into base plate through vacuum bag.
- Machined raised ring on base plate provides additional positive pressure seal.
- Designed with 1/4" (6.35mm) male NPT, works with TMI Quick Disconnect 1/4" plug or socket.
- TMI-VV is capable of operating temperatures up to 500°F (260°C)

### Specifications:

Construction:	2 piece: 1.75" round base plate, 1.5" knurled top
Material:	Anodized aluminum base, Stainless Steel top
Gasket:	Silicone: 1.40" O.D., 0.50" I.D., 0.08" Thick
Coupling Size:	1/4" (6.35mm) Male NPT
Assembly:	Threaded cutting edge
Service Temperature:	500°F (260°C)



### Application:

- The **TMI-VV** base plate is inserted under the vacuum bag film. Small slit is made in the vacuum bag film Inside the threaded center of the base plate. The knurled edge valve top piece is threaded through the vacuum bag film by hand into the base plate. Once the **TMI-VV** is hand tightened and locked in place it is ready for use. **Note:** Attach **TMI Quick Disconnect** 1/4" plug or socket to **TMI-VV** prior to bag film installation.

**Technology Marketing, Inc.**

P: 801.265.0111 • F: 801.265.0184

6122 Stratler Street • Salt Lake City, UT 84107 USA • [customerservice@tmi-slc.com](mailto:customerservice@tmi-slc.com) • [www.tmi-slc.com](http://www.tmi-slc.com)

**ISO 9001:2015 & AS9120B Certified**

Note: Data provided is for information only and does not constitute any warranty for the product as the conditions and varying methods of use are beyond our control. Technology Marketing Inc. shall not be liable for any special indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use or inability to use these materials. These materials are provided "as is" without warranty of any kind, either expressed or implied including, but not limited to the implied warranties of merchantability or fitness for a particular purpose