

TMI-CF500VB

High Temperature, High Elongation Bagging Film

Features:

- High temperature, high elongation bagging film made from PTFE.
- Suitable for cure cycles up on 500°F (260°C).
- One side has been treated to ensure good adhesion to sealant tapes.
- Designed for use with epoxy, polyimide, bismaleimide, and phenolic resin systems.
- Excellent for advanced composites where high temperature and flexible film are required.

Properties:

Technical Data:	Test Method:	Typical Value:
Max. use temperature		500°F (260°C)
Color		Yellow
Tensile Strength	ASTM D-882	4,300 psi
Tensile Modulus	ASTM D-882	55,000 psi
Film Material		PTFE

The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.

Availability:

- Standard Roll Size: 50" x .003" x 175'
- Max. width available: 56"
- (Other configurations may be available upon request. Minimums may apply.)

Storage:

- Store in original packaging and protect from the environment. Do not store vertically on end.

Health & Safety:

- Handling of these products must conform to individual company guidelines and health and safety regulations.

Technology Marketing, Inc.

P: 801.265.0111 • F: 801.265.0184

6122 Stratler Street • Salt Lake City, UT 84107 USA • customerservice@tmi-slc.com • www.tmi-slc.com

ISO 9001:2015 & AS9120B Certified

Note: Data provided is for information only and does not constitute any warranty for the product as the conditions and varying methods of use are beyond our control. Technology Marketing Inc. shall not be liable for any special indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use or inability to use these materials. These materials are provided "as is" without warranty of any kind, either expressed or implied including, but not limited to the implied warranties of merchantability or fitness for a particular purpose