

SV2000

Soft High Elongation Nylon Bagging Film

Features:

- Soft, high elongation, heat stabilized nylon bagging film.
- Designed to remain flexible and conforms to complex contours.
- Ideal for vacuum bagging advanced composite components that require a higher level of strength, stretchability, and will easily conform.
- Can be heat sealed for custom shape bag requirements.
- Compatible with most commonly used resin systems, with the exception of phenolic.

Properties:

Technical Data:	Test Method:	Typical Value:
Max. use temperature		400°F (204°C)
Color		Red
Tensile Strength	ASTM D-882	11,000 psi
Elongation (at break)	ASTM D-882	>450%

The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.

Availability:

- Standard Format: Sheeting, V-Sheeting, Lay-Flat Tubing
 - Roll Widths: 2"-84"
 - Standard Thickness: .002" & .003"
 - Standard Roll Length: 500'
(Other configurations may be available upon request. Minimums may apply.)
- **Storage:**
 - SV2000, is a hydrophilic or water-sensitive material, like all nylon films; moisture and water act as plasticizers. The level of moisture content at time of use is an important factor for successful performance. Store in original packaging and protect from the environment. Do not store vertically on end.

Health & Safety:

- Handling of these products must conform to individual company guidelines and health and safety regulations.

Technology Marketing, Inc.

P: 801.265.0111 • F: 801.265.0184

6122 Stratler Street • Salt Lake City, UT 84107 USA • customerservice@tmi-slc.com • www.tmi-slc.com

ISO 9001:2015 & AS9120B Certified

Note: Data provided is for information only and does not constitute any warranty for the product as the conditions and varying methods of use are beyond our control. Technology Marketing Inc. shall not be liable for any special indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use or inability to use these materials. These materials are provided "as is" without warranty of any kind, either expressed or implied including, but not limited to the implied warranties of merchantability or fitness for a particular purpose